

# EOS 5D Mark IV



## Pursue perfection

Flexibility without compromise, enabling you to pursue the perfect moment.



- A 30-megapixel sensor delivers images that are packed with detail, even in the brightest highlights and darkest shadows.
- Dual Pixel Raw is an alternative file format that lets photographers fine-tune image quality after it's been captured.
- Low-light performance is improved throughout the ISO sensitivity range, right up to the max ISO 32,000 setting (expandable to ISO 102,400).
- A Digital Lens Optimizer works together with Lens Aberration Correction to compensate for optical phenomena, including the camera's optical low-pass filter, for incredible image quality.

### Product Range



EOS 5D Mark IV



EOS 5DS



EOS 5DS R

**EOS 5D Mark IV**  
EOS 5DS  
EOS 5DS R  
EOS-1D X Mark II

## Technical Specifications

### IMAGE SENSOR

Type	36 mm x 24 mm CMOS
Effective Pixels	Approx. 30.4 megapixels
Total Pixels	Approx. 31.7 megapixels
Aspect Ratio	3:2
Low-Pass Filter	Built-in/Fixed
Sensor Cleaning	EOS integrated cleaning system
Colour Filter Type	Primary Colour

### IMAGE PROCESSOR

Type	DIGIC 6+
------	----------

### LENS

Lens Mount	EF (excludes EF-S / EF-M lenses)
Focal Length	Equivalent to 1.0x the focal length of the lens

### FOCUSING

Type	TTL-secondary image-forming phase-difference detection system with dedicated AF sensor
AF System/ Points	61 Point / max of 41 cross-type AF points inc 5 dual cross type at f/2.8 and 61 points / 21 cross-type AF points at f/8 <sup>(11)</sup> The number of cross-type AF points will differ depending on the lens.
AF working range	EV -3 - 18 (at 23°C & ISO100)
AF Modes	One Shot AI Focus AI Servo AF
AF Point Selection	Automatic selection: All 61 point AF (based on EOS iTR AF setting) Manual selection: Single point AF (selectable points 61, 15, 9 or cross type only points selectable) Manual selection: Single point Spot AF Manual selection: AF point Expansion 4 points (up, down, left, right) Manual selection: AF point Expansion surrounding 8 points Manual selection: Zone AF (all AF points divided into 9 focusing zones) Manual selection: Large Zone AF (all AF points divided into 3 focusing zones) AF points can be selected separately for vertical and horizontal shooting
Selected AF point display	transparent LCD in viewfinder and shown on Quick Control screen
AF Lock	Locked when shutter button is pressed half way or AF ON is pressed in One Shot AF mode. Using customised button set to AF stop in AI servo
AF Assist Beam	Emitted by an optional dedicated Speedlite
Manual Focus	Selected on lens
AF Microadjustment	Manual: Enter adjustment +/- 20 steps (wide and tele setting for zoom lenses) Adjust all lenses by same amount Adjust up to 40 lenses individually Adjustments remembered for lens by serial number

### EXPOSURE CONTROL

Metering modes	Approx. 150,000-pixel RGB+IR metering sensor, 252-zone metering. EOS Intelligent Subject Analysis system (1) Evaluative metering (linked to All AF point) (2) Partial metering (approx. 6.1% of viewfinder at centre) (3) Spot metering: Center spot metering (approx. 1.3% viewfinder at centre) AF point-linked spot metering not provided (4) Centre weighted average metering
Metering Brightness Range	EV 0 - 20 (at 23°C, ISO100, with evaluative metering)
AE Lock	Auto: In the One-Shot AF mode with evaluative metering, AE lock takes effect when focus is achieved Manual: By AE lock button in P, Av, Tv and M modes
Exposure Compensation	+/-5 EV in 1/3 or 1/2 stop increments (can be combined with AEB). +/-3 EV in 1/3 or 1/2 stop increments
AEB	
Anti-flicker shooting	Yes. Flicker detected at a frequency of 100 Hz or 120 Hz. Maximum continuous shooting speed may decrease
ISO Sensitivity <sup>(8)</sup>	Auto 100-32000 (in 1/3-stop or whole stop increments) ISO can be expanded to L:50, H1: 51200, H2: 102400,

### SHUTTER

Type	Electronically-controlled focal-plane shutter
Speed	30-1/8000 sec (1/2 or 1/3 stop increments), Bulb (Total shutter speed range. Available range varies by shooting mode)
Shutter Release	Soft touch electromagnetic release

### WHITE BALANCE

Type	Auto white balance with the imaging sensor
Settings	AWB (Ambience priority/White priority), Daylight, Shade, Cloudy, Tungsten light, White Fluorescent light, Flash, Custom, Colour Temperature Setting White balance compensation: 1. Blue/Amber +/-9 2. Magenta/ Green +/-9 Yes, 1 setting can be registered +/-3 levels in single level increments 3, 2, 5 or 7 bracketed images per shutter release Selectable Blue/Amber bias or Magenta/ Green bias
Custom White Balance	
WB Bracketing	

### VIEWFINDER

Type	Pentaprism
Coverage	Approx. 100%
(Vertical/Horizontal)	
Magnification	Approx. 0.71x <sup>(4)</sup>
Eyepoint	Approx. 21mm (from eyepiece lens centre)
Dioptre Correction	-3 to +1 m <sup>-1</sup> (dioptre)
Focusing Screen	Fixed, with information Transparent LCD overlay
Mirror	Quick-return half mirror
Viewfinder Information	AF information: Single/Spot AF points, AF Frame, AF status, Focus indicator, AF mode, AF point selection, AF point registration Exposure information: Shutter speed, aperture value, ISO speed (always displayed), AE lock, exposure level/compensation, flash metering, spot metering circle, exposure warning, AEB, metering mode, shooting mode Flash information: Flash ready, high-speed sync, FE lock, flash exposure compensation, red-eye reduction light. Image information: Card information, maximum burst (2 digit display), Highlight tone priority (D+), JPEG/RAW indicator, Dual Pixel RAW, Digital Lens Optimizer. Composition information: Grid, Electronic level Other information: Battery check, Warning symbol, Flicker Detection, drive mode, white balance Yes, with Depth of Field preview button On strap
Depth of field preview	
Eyepiece shutter	

### LCD MONITOR

Type	8.10 cm (3.2") Clear View LCD II, approx. 1620K dots
Coverage	Approx. 100%
Viewing Angle	Approx. 170° vertically and horizontally
(horizontally/vertically)	
Coating	Anti-reflection and Anti-smudge. Reinforced glass incorporated
Brightness Adjustment	Manual: Adjustable to one of seven levels Color Tone Adjunct: 4 settings
Touch-screen operations	Capacitive method with menu functions, Quick Control settings, playback operations, and magnified display. AF point selection in Live View and Movies, touch shutter is possible in Live View still photo shooting.
Display Options	(1) Quick Control Screen (2) Camera settings (3) Dual Axis Electronic Level (4) Custom Quick Control Screen

### FLASH

Modes	E-TTL II Auto Flash, Metered Manual
X-sync	1/200sec
Flash Exposure Compensation	+/- 3EV in 1/3 increments with EX series Speedlites
Flash Exposure Bracketing	Yes, with compatible External Flash
Flash Exposure Lock	Yes
Second Curtain Synchronisation	Yes
HotShoe/ PC terminal	Yes / Yes
External Flash Compatibility	E-TTL II with EX series Speedlites, wireless multi-flash support via camera menu screen
External Flash Control	

## Technical Specifications

### SHOOTING

#### Modes

Scene Intelligent Auto, Program AE, Shutter priority AE, Aperture priority AE, Manual (Stills and Movie), Bulb and Custom (x3)

#### Picture Styles

Auto, Standard, Portrait, Landscape, Fine Detail, Neutral, Faithful, Monochrome, User Defined (x3)

#### Colour Space

sRGB and Adobe RGB

#### Image Processing

Highlight Tone Priority  
Auto Lighting Optimizer (4 settings)  
Long exposure noise reduction  
High ISO speed noise reduction (4 settings)  
Lens optical correction<sup>(5)</sup>:  
- Peripheral illumination correction (during/after still photo shooting, during Video only)  
- Chromatic aberration correction (during/after still photo shooting, during Video only)  
- Distortion correction (during/after still photo shooting)  
- Diffraction correction (during/after still photo shooting)  
- Digital Lens Optimizer (during/after still photo shooting)  
Resize to M, S1, S2 or S3<sup>(6)</sup>  
Cropping: JPEG images can be cropped (Aspect ratios 3:2, 4:3, 16:9, 1:1)  
- 45 cropping sizes selectable, from 11% to 95% (diagonal)  
- Switch between vertical and horizontal cropping orientation  
- Cropping frame can be moved using touch screen operation  
RAW image processing<sup>(7)</sup>  
Multiple exposure  
Single, Continuous High, Continuous Low, Silent Single, Silent Continuous High, Silent Continuous Low, Self timer (2s+remote, 10s+remote)  
Max. Approx. 7fps. with full AF / AE tracking, speed maintained for up to unlimited number of JPEGs or 21 RAW images<sup>(1) (2) (10)</sup>  
Max. 4.3fps in Live View mode with AF Tracking  
Built-in, number of shots selectable from 1-99 or unlimited (Selectable interval time - 1sec to 99hr 59mins 59sec). Bulb timer possible (Selectable time - 1sec to 99hr 59mins 59sec)

#### Drive modes

Single, Continuous High, Continuous Low, Silent Single, Silent Continuous High, Silent Continuous Low, Self timer (2s+remote, 10s+remote)

#### Continuous Shooting

Max. Approx. 7fps. with full AF / AE tracking, speed maintained for up to unlimited number of JPEGs or 21 RAW images<sup>(1) (2) (10)</sup>

#### Interval timer

Max. 4.3fps in Live View mode with AF Tracking  
Built-in, number of shots selectable from 1-99 or unlimited (Selectable interval time - 1sec to 99hr 59mins 59sec). Bulb timer possible (Selectable time - 1sec to 99hr 59mins 59sec)

### LIVE VIEW MODE

#### Type

Electronic viewfinder with image sensor

#### Coverage

Approx. 100% (horizontally and vertically)

#### Frame Rate

29.97 fps (may increase when AF is performed)

#### Focusing

Manual Focus (Magnify the image 5x or 10x at any point on screen)  
Autofocus: Dual Pixel CMOS AF (Face Detection and Tracking AF, FlexiZone - Single, FlexiZone - Multi), available with all EF lenses and Touch shutter

#### Metering

Real-time evaluative metering with image sensor (315-zone)  
Partial metering (approx. 6.3% of Live View screen)  
Spot metering (approx. 2.7% of Live View screen)  
Center-weighted average metering  
Active metering timer can be changed

#### Display Options

4 levels available through INFO. button: No information, Basic shooting information, Advanced shooting information and Advanced shooting information with Histogram  
Multiple Exposure status also available in Multiple Exposure mode

### FILE TYPE - Stills

#### Still Image Type

JPEG: 3 compression options  
RAW: RAW, M-RAW, S-RAW and Dual Pixel RAW (14bit, Canon original RAW 2nd edition)  
Complies with Exif 2.30 and Design rule for Camera File system 2.0  
Complies with Digital Print Order Format [DPOF] Version 1.1  
Yes, any combination of RAW + JPEG possible, separate formats to separate cards possible including  
Dual Pixel RAW +JPEG

#### RAW+JPEG simultaneous recording

#### Image Size

#### JPEG:

3:2 ratio (L) 6720x4480, (M1) 4464x2976, (S1) 3360x2240, (S2) 1696x1280, (S3) 640x480  
4:3 ratio (L) 5952x4480, (M1) 3968x2976, (S1) 2976x2240, (S2) 1920x1280, (S3) 720x480  
16:9 ratio (L) 6720x3776, (M1) 4464x2512, (S1) 3360x1888, (S2) 1920x1080, (S3) 720x408  
1:1 ratio (L) 4480x4480, (M1) 2976x2976, (S1) 2240x2240, (S2) 1280x1280, (S3) 480x480

#### RAW:

(RAW) 6720x4480, (M-RAW) 5040x3360, (S-RAW) 3360x2240

New folders can be manually created and selected

(1) Consecutive numbering

(2) Auto reset

(3) Manual reset

#### Folders

#### File Numbering

### EOS Movie

#### Movie Type

MOV Video: 4K (17-9) 4096 x 2160 - Motion JPEG (internal recording only), Full HD - MPEG4 AVC / H.264 variable (average) bit rate, Audio: Linear PCM

MP4 Video: Full HD (16-9) 1920 x 1080 - MPEG4 AVC/H.264, Audio: AAC

#### Movie Size

4K (17-9) 4096 x 2160 (29.97, 25, 24, 23.98 fps) Motion JPEG  
Full HD (16-9) 1920 x 1080 (59.94, 50, 29.97, 25, 23.98 fps) intra or inter frame (13)

Full HD (16-9) 1920 x 1080 HDR (29.97, 25 fps) inter frame (13)

Full HD (16-9) 1920 x 1080 (29.97, 25) lite inter frame

HD (16-9) 1280 x 720 (119.9, 100 fps) intra frame

4K - YCbCr4:2:2 (8 bit)

Full HD / HD - YCbCr4:2:0 (8 bit)

4K and Full HD - Max duration 29min 59sec. (excluding High Frame Rate movies). No 4 GB file limit with exFAT CF card

MOV Video: HD - 1280 x 720 at 100fps or 119.9fps

Recorded as 1/4-speed slow motion movie

Single scene maximum recording up to 7 min 29 sec.

8.8 megapixel JPEG still image frame grab from 4K movie possible

MOV:

4K (29.97p/25.00p/24.00p/23.98p): Approx. 500 Mbps

Full HD (59.94p/50.00p)/ALL-I: Approx. 180 Mbps

Full HD (59.94p/50.00p)/IPB: Approx. 60 Mbps

Full HD (29.97p/25.00p/24.00p/23.98p)/ALL-I: Approx. 90 Mbps

Mbps

Full HD (29.97p/25.00p/24.00p/23.98p)/IPB (Standard):

Approx. 30 Mbps

HD (119.9p/100.0p)/ALL-I: Approx. 160 Mbps

MP4:

Full HD (59.94p/50.00p)/IPB (Standard): Approx. 60 Mbps

Full HD (29.97p/25.00p/24.00p/23.98p)/IPB (Standard):

Approx. 30 Mbps

Full HD (29.97p/25.00p)/IPB (Light): Approx. 12 Mbps

Built-in monaural microphone (48KHz, 16 bit x 2 ch)

External monitor only, External Monitor only without information display or Simultaneous on camera and external monitor

Full HD recording only, uncompressed YCbCr 4:2:2, 8-bit, sound output via HDMI is also possible

#### Microphone

#### HDMI Display

#### HDMI Output

#### Focusing

Dual Pixel CMOS AF with Face Detection and Tracking AF, Movie Servo AF

Manual Focus

#### ISO

4K - Auto: 100-12800, H: 25600, H1: 32000, H1: 51200,

H2: 102400,

Full HD / HD - Auto: 100-25600, H: 32000, H1: 51200, H2:102400

#### Built-in GPS

#### Geotag Information

#### Positioning Modes

Longitude, Latitude, Elevation, Coordinated Universal Time

Mode 1: Camera continues to receive GPS signals at regular intervals when power is switched off

Mode 2: GPS is switched off when power is switched off

Intervals of 1 sec., 5 sec., 10 sec., 15 sec., 30 sec., 1 min.,

2 min. or 5 min

#### Position Update Timing

## Technical Specifications

<b>Position Accuracy</b>	Within approx. 30 m/98.4 ft (Based on good GPS satellite reception conditions on a clear day with no surrounding obstructions)	<b>DIRECT PRINT</b>	
<b>Compatible Satellite Navigation Systems</b>	<ul style="list-style-type: none"> <li>• GPS satellites (USA)</li> <li>• GLONASS satellites (Russia)</li> <li>• Quasi-Zenith Satellite Michibiki (Japan)</li> </ul>	<b>PictBridge</b>	Yes (Via Wireless LAN only)
<b>Log Files Format</b>	NMEA Format. One log file per day based	<b>STORAGE</b>	
<b>Log File Usage</b>	Transfer log data to memory card and copy it to a computer	<b>Type</b>	1x CompactFlash Type I (UDMA 7 compatible) (Incompatible with Type II and Microdrive) 1x SD/SDHC/SDXC and UHS-I
<b>Digital Compass</b>	Use Map Utility to append the log file to the images Not provided	<b>SUPPORTED OPERATING SYSTEM</b>	
<b>OTHER FEATURES</b>		<b>PC &amp; Macintosh</b>	Windows 7 (excl. Starter Edition) Windows 8 and Windows 10 OS X v10.7-10.11
<b>Custom Functions</b>	17 Custom Functions with 46 settings	<b>SOFTWARE</b>	
<b>Metadata Tag</b>	User copyright information (can be set in camera) Image rating (0-5 stars) IPTC data (registered with EOS Utility) Image transfer with caption (Caption registered with EOS Utility)	<b>Image Processing</b>	Digital Photo Professional 4.5 or later (RAW Image Processing)
<b>LCD Panel / Illumination</b>	Yes / Yes	<b>Other</b>	EOS Utility 3.5 or later (inc. Remote Capture ), Picture Style Editor, Map Utility, EOS Lens Registration Tool, EOS Web Service Registration Tool, Canon Camera connect app (iOS/ Android)
<b>Water/ Dust resistance</b>	Yes	<b>POWER SOURCE</b>	
<b>Voice Memo</b>	No	<b>Batteries</b>	Rechargeable Li-ion Battery LP-E6N (supplied) / LP-E6
<b>Intelligent Orientation Sensor</b>	Yes	<b>Battery life</b>	Approx. 900 shots (at 23°C) <sup>(6)</sup> Approx. 850 (at 0°C)
<b>Playback zoom</b>	1.5x - 10x in 15 steps	<b>Battery Indicator</b>	6 levels + percentage
<b>Display Formats</b>	(1) Single image (2) Single image with information (2 levels) Basic - Shooting information (shutter speed, aperture, ISO and Image quality) Detailed - Shooting information (shutter speed, aperture, ISO, metering, Image, quality and file size), Lens information, Brightness and RGB histogram, White balance, Picture Style, Color space and noise reduction, Lens optical correction, GPS information (3) 4 image index (4) 9 image index (5) 36 image index (6) 100 image index (7) Jump Display (1, 10 or 100 images, Date, Folder, Movies, Stills, Protected images, Rating) (8) Movie edit (9) RAW processing (10) Rating	<b>Power saving</b>	Power turns off after 1, 2, 4, 8, 15 or 30mins
<b>Slide Show</b>	Image selection: All images, by Date, by Folder, Movies, Stills, Protected images or Rating Playback time: 1/2/3/5/10 or 20 seconds Repeat: On/Off	<b>Power Supply &amp; Battery Chargers</b>	Battery charger LC-E6E (supplied), Battery charger LC-E6, AC Adapter AC-E6N and DC Coupler DR-E6, AC Adapter Kit ACK-E6N/ACK-E6, Car Battery Charger CBC-E6
<b>Histogram</b>	Brightness: Yes RGB: Yes	<b>PHYSICAL SPECIFICATIONS</b>	
<b>Highlight Alert</b>	Yes	<b>Body Materials</b>	Magnesium Alloy body and polycarbonate with glass fiber Prism cover
<b>Image Erase</b>	Single image, Selected images, Folder, Card	<b>Operating Environment</b>	0 - 40 °C, 85% or less humidity
<b>Image Erase Protection</b>	Erase protection of Single image, Folder or Card	<b>Dimensions (WxHxD)</b>	150.7 x 116.4 x 75.9 mm
<b>Self Timer</b>	2 or 10 sec.	<b>Weight (body only)</b>	Approx. 890 g
<b>Menu Categories</b>	(1) Shooting menu 1 - 6 (2) AF Menu 1 - 5 (3) Playback menu 1 - 3 (4) Setup menu 1 - 5 (5) Custom Functions menu 1 - 5 (6) My Menu (1 - 5 user selectable)	<b>ACCESSORIES</b>	
<b>Menu Languages</b>	25 Languages English, German, French, Dutch, Danish, Portuguese, Finnish, Italian, Norwegian, Swedish, Spanish, Greek, Russian, Polish, Czech, Hungarian, Romanian, Ukrainian, Turkish, Arabic, Thai, Simplified Chinese, Traditional Chinese, Korean and Japanese	<b>Viewfinder</b>	EyeCup Eg, Eg-series Dioptic Adjustment Lens with Rubber Frame Eg, Anti Fog Eyepiece Eg, Angle Finder C Wireless File Transmitter WFT-E7B
<b>Firmware Update</b>	Update possible by the user (Camera, Lens, WFT, External Speedlite)	<b>Wireless File Transmitter</b>	
<b>INTERFACE</b>		<b>Lenses</b>	All EF lenses (excluding EF-S / EF-M lenses)
<b>Computer</b>	SuperSpeed USB 3.0	<b>Flash</b>	Canon Speedlites (90EX, 220EX, 270EX, 270EX II, 320EX, 380EX, 420EX, 430EX, 430EX II, 430EX III 550EX, 580EX, 580EX II, 600EX, 600EX-RT, 600EX-II-RT, Macro-Ring-Lite MR-14EX, Macro Ring Lite MR-14EX II, Macro Twin Lite MT-24EX, Speedlite Transmitter ST-E2, Speedlite Transmitter ST-E3-R1)
<b>WiFi</b>	Wireless LAN (IEEE802.11b/g/n), (2.4 GHz only), with Dynamic NFC support <sup>(12)</sup> Features supported - FTP/FIPS, EOS Utility, SmartPhone, Upload to Web, Wireless printing	<b>Remote Controller/ Switch</b>	Remote control with N3 type contact, Wireless Controller LC-5 and Speedlite 600EX-II-RT
<b>Other</b>	HDMI mini out (Type C, HDMI-CEC compatible), External Microphone In / Line In (Stereo mini jack), Headphone socket (Stereo mini jack), N3-type terminal (remote control terminal)	<b>Other</b>	BG-E20 battery grip, Hand Strap E2, Connect Station CS100
		<b>Footnotes</b>	
		<sup>(1)</sup> Large/Fine resolution	
		<sup>(2)</sup> Based on Canon's testing conditions, JPEG, ISO 100, Standard Picture Style. Maximum fps and buffer capacity may be reduced depending on the camera settings, light level, subject, memory card brand and capacity, image recording quality, ISO speed, drive mode, Picture Style, Custom functions etc.	
		<sup>(3)</sup> Not possible with M-RAW and S-RAW	
		<sup>(4)</sup> with 50mm lens at infinity, -1m <sup>-1</sup> dpt	
		<sup>(5)</sup> Viewfinder shooting. Based on the CIPA Standard and using the battery supplied with the camera, except where indicated	
		<sup>(6)</sup> Frame grab images from 4K movies and images shot in S3 quality cannot be resized	
		<sup>(7)</sup> RAW image processing during image Playback only with RAW and Dual Pixel RAW only	
		<sup>(8)</sup> Recommended Exposure Index	
		<sup>(10)</sup> Figures quoted are when used with UDMA 7 Compact flash memory card	
		<sup>(11)</sup> The number of AF points, cross-type AF points, and dual cross-type AF points vary depending on the lens used	
		<sup>(12)</sup> Wi-Fi use may be restricted in certain countries or regions	
			All data is based on Canon standard testing methods except where indicated. Subject to change without notice.

## Pursue perfection

Flexibility without compromise, enabling you to pursue the perfect moment.

Sales Start Date: September 2016



### Product Details:

Product Name	Mercury Code	EAN Code	Recommended Retail Price
EOS 5D Mark IV Body	1483C026AA	8714574645964	£3629.99 / €4899.99

### Optional Accessories:

Product Name	Mercury Code	EAN Code	Recommended Retail Price
Battery Grip BG-E20	1485C001AA	4549292075946	£329.99 / €399.99
Directional Stereo Microphone DM-E1	1429C001AA	4549292065732	£274.99 / €369.99
Speedlite 600EX II-RT	1177C003AA	4549292059441	£539.99 / €719.99
Wireless File Transmitter: WFT-E7B Ver.2	5754B015AA	4549292023329	£769.99 / €899.99
Protecting Cloth PC-E1	1883C001AA	4549292083392	£24.99 / €32.99

### Measurement / Logistic Information:

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (mm)	Width (mm)	Height (mm)	Net Weight (kg)	Gross Weight (kg)
EOS 5D Mark IV Body	1483C026AA	EA	Each	1	249	183	151	1.217	1.5932
		CT	Carton	6	471	382	288	9.3792	10.3901
		EP	Euro Pallet	72	1200	800	1014		135
			Layers per Pallet	3					
			Cartons per Layer	4					

## Pursue perfection

Flexibility without compromise, enabling you to pursue the perfect moment.



### Measurement / Logistic Information:

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (mm)	Width (mm)	Height (mm)	Net Weight (kg)	Gross Weight (kg)
Battery Grip BG-E20	1485C001AA	EA	Each	1	162	94	123	0.392	0.525
		CT	Carton	6	490	260	167	3.15	3.752
		EP	Euro Pallet	216	1200	800	115.2		145
			Layers per Pallet	6					
			Cartons per Layer	6					
Directional Stereo Microphone DM-E1	1429C001AA	EA	Each	1	195.5	135.5	82.5	0.120	0.266
		CT	Carton	6	413	293	261	1.599	2.037
		EP	Euro Pallet	144	1200	800	1190		52.1
			Layers per Pallet	4					
			Cartons per Layer	6					
Speedlite 600EX II-RT	1177C003AA	EA	Each	1	148	112	165	0.585	0.7667
		CT	Carton	6	524	362	200	4.6002	5.5052
		EP	Euro Pallet	120	120	80	115		111
			Layers per Pallet	5					
			Cartons per Layer	4					
Wireless File Transmitter: WFT-E7B Ver.2	5754B015AA	EA	Each	1	129	59	173		0.4
		CT	Carton	20	536	318	222		8.6
		EP	Euro Pallet	320	1200	800	1038		147
			Layers per Pallet	4					
			Cartons per Layer	4					
Protecting Cloth PC-E1	1883C001AA	EA	Each	1	120	187	1	0.113	0.122
		CT	Carton	6	326	306	232	0.732	1.423
		EP	Euro Pallet	144	1200	800	1078		44.20
			Layers per Pallet	4					
			Cartons per Layer	6					

### What's in the box?

- EOS 5D Mark IV
- Battery Pack LP-E6N
- Battery Charger LC-E6E
- Eyecup Eg
- Wide Strap
- Interface Cable IFC-150U II
- Cable Protector
- EOS Digital Solution Disk